



Phone (866)463-2910
Email: sales@fastenersolutions.com

Nickel Grade Anti-Seize

Nickel and Graphite Based Anti-Seize Compound

Nickel Grade Anti-Seize is used wherever extreme service conditions exist. It is a premium quality Anti-Seize Compound and lubricant designed especially for maximum resistance to the most corrosive and extreme temperature environments. Performs to temperatures of 2600 °F.

Nickel Grade Anti-Seize is composed of pure colloidal nickel and high purity graphite flakes dispensed in a superior high-performance petroleum carrier enhanced with the latest rust, corrosion and extreme pressure additives. It does not contain any copper, lead, or molybdenum disulfide.

Nickel Grade Anti-Seize will not poison catalyst beds, reaction chambers, or special alloy fittings and can be used with anhydrous ammonia, acetylene, and other vinyl monomers. Meets the performance requirements of MIL-PRF-907F.

Features & Benefits:

- Offers maximum protection from acids, caustics, corrosive chemicals and extreme heat
- Eliminates galling and cold welding
- Reduces friction and lowers torque
- Speeds assembly and disassembly
- Provides a nickel plating as a barrier between metal surfaces
- Protects against corrosion and oxidation

APPLICATIONS:

- All nuts and bolts, bushings, centers, cam rollers, conveyors, couplings, dies, drills and taps, fittings, flanges, gears and motors, keyways, press fits, pumps, shafts, sleeves and slides, spark plugs, valves, wristpins and more.

Service Recommendations:

- -300°F to 2600°F
- Not suitable for use with oxygen or concentrated chlorine

Shelf Life:

- Nickel Grade Anti-Seize has a shelf life of 5 years or more when stored in a closed container. Shelf life may be much longer depending upon storage location and conditions. Store with container tightly sealed in a cool dry place for optimum shelf life. If slight separation occurs, stir product.